

1. **Name and identification code:** 40 mm translucent cellular polycarbonate sheets, XT Lux.

2. **Name and address of manufacturer:** HUURRE IBÉRICA S.A.U.
Carrer Serinyà 43, Polígono Industrial El Trust
E-17244 Cassà de la Selva, Girona, España

3. **Intended use:** Internal and external use on roof, façade and interior partitions.

4. **System for assessing and verifying the constancy of performance:** System 3.

5. **Declared benefits:**

Essential features	Performance			Harmonising standard
Fire reaction	B,s1-d0			EN 16153:2013+A1:2015
Fire resistance	PND			
Water vapour permeability	3,8 x 10 ⁻⁵ mg / m·h·Pa			
Air/water vapour permeability	Conforme			
Emission of dangerous substances	PND			
Dimensional tolerances	Conforme			
Thermal transmittance	U=1.06 W/m²Kº			
Light transmittance, solar transmittance and solar factor	LT%	ST%	SHGC	
(ASHREA STANDARD 74-1988)	39	42	0,46	
Fixing resistance	Fixing method (see technical manual)			
Thermal dilatation	0.065 mm/mºK			
Durability	ΔA			
Durability	ΔA			

6. The performance of the product identified in point 1 is in accordance with the performance declared in point 5.

7. This declaration of performance is issued in accordance with Regulation (EU) No. 305/2011 under the sole responsibility of the manufacturer indicated in point 2.

Signed for and on behalf of the manufacturer by:

Josep Jordan (C.E.O)

Signature

Place and date of issue: Cassà de la Selva, 11 de junio de 2026

